

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/049833 A1

- (51) International Patent Classification⁷: **A23L 2/40, 2/54** (72) **Inventor: O'CONNELL, John**; Unilever PLC, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).
- (21) International Application Number:
PCT/EP2003/012606 (74) **Agent: THACKER, Michael, Anthony**; Unilever PLC, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).
- (22) International Filing Date:
10 November 2003 (10.11.2003)
- (25) Filing Language: English (81) **Designated States (national)**: AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.
- (26) Publication Language: English
- (30) **Priority Data**:
02258270.4 29 November 2002 (29.11.2002) EP (84) **Designated States (regional)**: ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) **Applicant (for AE, AG, AU, BB, BZ, CA, CY, EG, GB, GD, GH, GM, IE, IL, KE, LC, LK, LS, MN, MW, NZ, OM, PG, SC, SD, SG, SL, SZ, TT, TZ, UG, VC, ZA, ZM, ZW only)**: UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB).
- (71) **Applicant (for AL, AM, AT, AZ, BA, BE, BF, BG, BJ, BR, BY, CF, CG, CH, CI, CM, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, FR, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IS, IT, JP, KG, KP, KR, KZ, LR, LT, LU, LV, MA, MC, MD, MG, MK, ML, MR, MX, MZ, NE, NI, NL, NO, PH, PL, PT, RO, RU, SE, SI, SK, SN, SY, TD, TG, TJ, TM, TN, TR, UA, UZ, VN, YU only)**: UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).
- (71) **Applicant (for IN only)**: HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: BEVERAGE WITH FOAM MAINTAINING SYSTEM

(57) **Abstract**: A beverage product comprises a container holding a liquid beverage component and sufficient nitrogen gas to give a gas pressure in the head space of at least 3.3 bar at 5°C, said liquid beverage comprising an organoleptically acceptable foam-maintaining system such that when the liquid beverage is poured from the container a foam is generated, the volume of which is maintained at greater than 80% of its initial volume for a period of at least 10, preferably at least 30 minutes. The initial volume of the foam may be less than 20% of the volume of the liquid beverage. The foam-maintaining system may comprise octenylsuccinic acid modified starch, and at least one surface active agent selected from the group consisting of acyl lactylate salts, proteins, protein hydrolysates, sucrose esters, and mixtures thereof.

- 1 -

BEVERAGE WITH FOAM MAINTAINING SYSTEM

The present invention relates to beverage products and in particular of foaming beverage products.

5

There are many examples of foaming beverages which are produced by the use of inserts inside a pressurised can. In the United Kingdom many canned beers, stouts and lagers are sold in cans which contain a so-called "widget" which operates after the can is opened to give a head on the drink which is said to be comparable to the head produced on draught drinks dispensed in EP-A-360284, EP-A-577284, US-A-4996823, US-A-5009901, WO-A-9324384, WO-A-9504689. Examples of non-alcoholic pressurised beverages which are pressurised with nitrous oxide and/or carbon dioxide are described in US-A-6403137 and GB-A-2299978.

15

Beverages that are packaged in a closed container in the presence of carbon dioxide or nitrous oxide and nitrogen are described in EP-A-745329 and EP-A-1034703. Foaming cappuccino coffee products can be made by adding to the coffee drink a creamer comprising protein, lipid and carrier and optionally a modified starch emulsifier or a surfactant as is described in US-A-6168819. Effervescent beverages which are intended to be dispensed directly into the mouth of the consumer are described in WO-A-02070371 and WO-A-02070372.

25

A first aspect of the present invention provides a beverage product comprising a container holding a liquid beverage component and sufficient nitrogen gas to give a gas pressure in the head space of at least 3.3 bar at 5°C, said liquid beverage

- 2 -

comprising an organoleptically acceptable foam-maintaining system such that when the liquid beverage is poured from the container a foam is generated, the volume of which is maintained at greater than 80% of its initial volume for a period of at least 10, preferably at least 30 minutes.

Preferably, the initial volume of the foam is less than 20% of the volume of the liquid beverage.


10 The container should be of sufficient strength that it can hold the pressure of the nitrogen gas inside it and should be impermeable to nitrogen gas. The container may be made of metal e.g., aluminium or steel, a plastic material for example polyethylene terephthalate or glass. The pressure of the gas
15 in the head space within the container should preferably be in the range 3.3 to 6 bar at 5°C. The nitrogen gas may be introduced into the container in the form of liquid nitrogen. The term "nitrogen gas" as used herein is intended to include pure nitrogen gas or gas mixtures that are predominantly
20 comprised of nitrogen. Preferably the nitrogen gas has purity of >97%.

The liquid beverage component may be any consumable liquid. Examples of suitable liquids include optionally flavoured water,
25 optionally flavoured milk, fruit flavoured liquids, tea or tea flavoured liquids, coffee or coffee flavoured liquids, chocolate, chocolate flavoured liquids, fruit smoothies or alcoholic or alcohol-free drinks such as cream liqueurs or cocktails.

- 3 -

In a preferred embodiment, the foam-maintaining system of the liquid beverage comprises 0.25 to 3.0% by weight of the liquid beverage component of octenylsuccinic acid modified starch, and at least one surface active agent selected from the group consisting of acyl lactylate salts, proteins, protein hydrolysates and sucrose esters and mixtures thereof.


The octenylsuccinic acid modified starch may be prepared by forming a covalent complex of a hydrophilic waxy maize starch with an octenylsuccinic acid moiety preferably its anhydride. The production of the octenylsuccinic acid modified starch is shown in the reaction scheme below.



- 4 -

Preferably the octenylsuccinic acid is a carboxy substituted undecenoic acid of formula

5



ie 3-carboxy-undec-5-enoic acid

10

The percentage molar substitution of octenylsuccinic acid groups may be in the range of 1.9 to 3%, preferably around 2.2%. The molecular weight of the octenylsuccinic acid modified starch is preferably in excess of 100,000 kDa.

15

The octenylsuccinic acid modified starch preferably comprises 0.75 to 1.5% by weight of the liquid beverage component. Suitable octenylsuccinate acid modified starch include those available from National Starch under the trade names Purity 2000, Purity 1773, Purity 539 and N-Creamer 46. A particularly preferred octenylsuccinic acid modified starch is available commercially from National Starch under the trade name N-Creamer 46

25 The viscosity of the liquid beverage component is preferably in the order of 1.5 to 100 mPa.s⁻¹, more preferably 30 to 60 mPa.s⁻¹ under low shear conditions (0.15 s⁻¹) at 5°C.

The acyl moiety of the acyl lactylate salt preferably contains 8 to 16 preferably 10 to 14 more preferably around 12 carbon atoms. The acyl lactylate salt may be a sodium or calcium salt.

30

- 5 -

Preferred acyl lactylate salts include calcium stearoyl lactylate and sodium stearoyl lactylate and mixtures thereof. The acyl lactylate salt preferably comprises 0.005 to 1 %, more preferably 0.01 to 0.5% by weight of the liquid beverage.

5

Suitable proteins and protein hydrolysates are those contained in or derived from milk for example caseinate salts such as sodium caseinate, whey protein isolates or milk protein hydrolysates. The protein and/or protein hydrolysate preferably
10 comprises 0.01 to 0.5 %, more preferably 0.1 to 0.3% by weight of the liquid beverage.

Sucrose esters are esters prepared from sucrose and fatty acids derived from edible fats and oils. Preferred sucrose esters are
15 predominantly monoesters. The fatty acid moiety preferably contains 8 to 16 carbon atoms. Suitable fatty acids include caprylic acid, lauric acid, myristic acid, palmitic acid, stearic acid and mixtures thereof. Suitable sucrose esters are commercially available from Ryoto under the trade names P-1570
20 (70% monoester with fatty acids derived from vegetable oils containing 70% palmitic acid) and M-1695 (80% monoester with fatty acids derived from vegetable oils containing 95% myristic acid). The sucrose ester preferably comprises 0.02 to 0.4%, more preferably 0.05 to 0.3% of the liquid beverage.

25

In preferred beverage products of the present invention the surface active agent comprises an acyl lactylate salt either alone or in combination with a sucrose ester, a protein or a protein hydrolysate.

- 6 -

The surface tension of the liquid beverage component should be in the order of 65 to 20 N.m⁻², more preferably 40 to 20 N.m⁻².

5 The beverages of the present invention may contain additional constituents. Examples of suitable additional constituents include:-

- (a) sweeteners for example natural sweeteners such as sugars (glucose, fructose, sucrose or corn syrup) or artificial
10 sweeteners such as saccharin, aspartame or acesulfam.
- (b) Preservatives for example benzoate or sorbate salts
- (c) Antioxidants for example ascorbic acid or salts thereof or tocopherols
- (d) Flavour enhancers for example maltol
- 15 (e) Flavourings for example fruit flavours or vanilla
- (f) pH adjusting agents for example sodium bicarbonate
- (g) viscosity adjusting agents for example propylene glycol alginate, carboxymethyl cellulose, high methoxy pectin and/or gums such as guar gum

20

A second aspect of the present invention provides a method of making a beverage product comprising a container holding a liquid beverage component and nitrogen gas, said liquid beverage comprising an organoleptically acceptable foam-maintaining
25 system, said method comprising the steps of:-

- incorporating the organoleptically acceptable foam-maintaining system into the liquid beverage,
- placing the liquid beverage into the container,

- 7 -

adding sufficient liquid nitrogen to the container to provide
a head space pressure of 3.3 to 6 bar at 5°C in the
container after sealing, and
sealing the container.

5

A third aspect of the present invention provides a method of
making a beverage product comprising a container holding a
liquid beverage component and nitrogen gas, said liquid beverage
comprising octenylsuccinic acid modified starch, and at least
10 one surface active agent selected from the group consisting of
acyl lactylate salts, proteins, protein hydrolysates and sucrose
esters and mixtures thereof, said method comprising the steps
of:-

incorporating the octenylsuccinic acid modified starch and
15 the at least one surface active agent into the liquid
beverage,
placing the liquid beverage into the container,
adding sufficient liquid nitrogen to the container to provide
a head space pressure of 3.3 to 6 bar at 5°C in the
20 container after sealing, and
sealing the container.

The contents of the sealed container may be sterilised after
sealing by the application of heat for example by pasteurisation
25 or retorting. Alternatively the product may be subjected to
microfiltration or may be filled aseptically.

The present invention provides a beverage which is retained
under pressure inside the container before the container is

- 8 -

opened but when the nitrogen becomes supersaturated after the container is opened, comes out of solution and forms a stable foam on top of the liquid beverage. In the beverage products of the present invention no widget is required to achieve this. The
5 presence of the foam on top of the dispensed liquid beverage provides a pleasant drinking experience (eg a pleasant taste and creamy mouthfeel) to the consumer as the beverage is consumed. The product may be consumed straight from the container but is preferably poured into a drinking vessel for
10 example a glass before consumption.

The invention will be illustrated by the following non-limiting examples

15

Example 1

A milked tea beverage was made as described below.

- 1) Black tea leaf tea (0.6kg) was extracted with water (18L) at
20 90 \pm 1°C for 3 minutes. The infusion was then passed through a 20 mesh screen, followed by a 150 mesh screen and cooled to 20-30°C. The infusion was then clarified using a centrifuge.
- 2) Sugar (5.5kg) was dissolved in hot water (6L), sterilised by
25 UV treatment and added to the tea extract.
- 3) UHT-treated skimmed milk (10.6kg) was added to the resulting mixture
- 4) Sodium ascorbate (0.05kg) was dissolved in water (2L) and the solution added to the mixture.

- 9 -

- 5) Water was added to a volume of 100L
- 6) The mixture was homogenised at 60-70°C @ 200 kgf.cm⁻² and heated to 85°C
- 7) Skimmed milk powder (1.106kg) was added and mixed at
- 5 13,500rpm for 2 minutes.
- 8) Sodium stearoyl lactylate (0.5kg) was added and mixed at 13,500 rpm for 2 minutes
- 9) N-Creamer 46 modified starch (1kg - ex National Starch) was added and mixed at 13,500 rpm for 2 minutes at 65°C.
- 10 10) The resulting solution was cooled to 10°C and maltol (0.03kg) was added The mixture (<295ml) was filled into standard 330ml beverage cans and sufficient liquid nitrogen was injected into the cans to give a head space pressure of 3.5 ± 0.2 bar at 5°C. The cans were then rapidly sealed.
- 15 11) The sealed cans were then retorted at 140°C for 5 minutes

The resulting beverage contained the following constituents

Constituent	Amount
Water	to 100%
UHT milk	10.60 %
Granulated sugar	5.5%
Tea solids	0.2%
Skimmed milk powder	1.16%
Tea flavour mix 06	0.16%
Sodium ascorbate	0.05%
Maltol	0.03%
N-Creamer 46	1.0%
Sodium stearoyl lactylate	0.5%

- 10 -

Example 2

A tea beverage was made as described below.

- 5 (1) Leaf tea (0.65 kg) was extracted with water (90L) at $90 \pm 1^\circ\text{C}$ for 5 min. The infusion was then passed through 4 layers of muslin cloth and the temperature was held at 70°C .
- (2) Sodium bicarbonate (0.01 kg) was dissolved in the filtered infusion
- 10 (3) Sugar (3.9 kg) was dissolved in the infusion at 70°C by stirring gently for 1 minute.
- (4) Caramel (0.1kg) was added to the infusion at 70°C
- (5) Sodium stearyl lactylate (0.5kg) added and mixed at 13,500 rpm for 2 minutes
- 15 (6) N-Creamer 46 starch (1kg) added and mixed at 13,500 rpm for 2 minutes at 65°C
- (7) The resulting solution was cooled to 10°C
- (8) Maltol (0.03kg) was added
- (9) Sodium ascorbate (0.05kg) was dissolved in water (2L) and
20 added to the mixture
- (10) Tea aroma concentrate (2 kg) was added and the mixture was made up to 100l with water.
- (11) The beverage mixture (<295ml) was filled into standard
25 330ml aluminium cans
- (12) Liquid nitrogen was injected in order to give a head space pressure of 3.5 ± 0.2 bar at 5°C and the cans were sealed rapidly.
- (13) The mixture was then retorted at 140°C for 5 minutes.

- 11 -

The resulting beverage contained the following constituents

Constituents	Amount
Water	to 100%
Tea solids	0.21%
Sugar	3.9%
Tea aroma concentrate	2.0%
Sodium ascorbate	0.05%
Sodium bicarbonate	0.01%
N-creamer 46	1.0%
Sodium stearyl lactylate	0.5%
Maltol	0.03%
Caramel	0.1%

5

Example 3

An Irish coffee-type beverage was made as described below.

- (1) Water (81.2 kg) was heated to 75°C
- 10 (2) Sugar (3.5kg) was added and completely dissolved at 70°C
- (3) A mixture of sodium stearyl lactylate (0.05kg), calcium stearyl lactylate (0.05kg) and sucrose monoesters (0.2kg) was added and mixed at 13,500 rpm at 70°C
- (4) Skim milk powder (1.0kg) was added and mixed at 13,500 rpm
15 at 70°C
- (5) N-Creamer 46 (1.0 kg) was added and mixed at 13,500 rpm at 70°C

- 12 -

- (6) Instant coffee powder (0.8 kg) was added and dissolved at 60°C
- (7) The mixture was cooled to ambient temperature and whiskey (12.2kg) was added
- 5 (8) The beverage (<295ml) was placed in a standard aluminium can (330ml) and sufficient liquid nitrogen was added to give a head pressure of 3.5 ± 0.2 bar at 5°C and can was sealed rapidly. Note. The product was filled and nitrogenated under aseptic conditions.

10

The resulting beverage contained the following constituents

Constituent	Amount
water	to 100%
sugar	3.50%
Sodium stearyl lactylate	0.05%
Calcium stearyl lactylate	0.05%
Sucrose monoesters	0.20%
Skimmed milk powder	1.0%
N-creamer 46	1.0%
coffee	0.80%
whiskey	12.20%

Example 4

15

A raspberry flavoured smoothie type beverage was made as described below.

- (1) Water (90 kg) is heated to 75°C

- 13 -

- (2) Sugar (4 kg) is added and completely dissolved at 70°C
- (3) Sodium stearoyl lactylate (0.5 kg) is added and mixed at 13,500 rpm at 70°C
- 5 (4) Skim milk powder (1 kg) is added and mixed at 13,500 rpm at 70°C
- (5) N-Creamer 46 (1 kg) is added and mixed at 13,500 rpm at 70°C
- (6) pH of solution is increased to pH 7.0 using 1.0M NaOH
- 10 (7) Cooled to ambient temperature and raspberry juice(10 kg) is added. The pH of the solution is maintained at pH 6.5 with the addition of 1.0M NaOH
- (8) The beverage (<295ml) was placed in a standard aluminium can (330mL).
- 15 (9) Sufficient liquid nitrogen was added to give a head pressure of 4 bar at 5°C and the can was sealed rapidly.
- (10) The can was retorted at 121°C for 5min.

The resulting beverage contained the following constituents

20

Constituent	Amount
Water	to 100%
Raspberry juice	10%
Sugar	4%
N-creamers 46	1%
Sodium stearoyl lactylate	0.5%
Skim milk powder	1%
Vanilla	0.05%

- 14 -

Example 5

5 A milked tea beverage was made as described below.

- (1) Black tea leaf tea (0.6kg) was extracted with water (80L) at $90 \pm 1^\circ\text{C}$ for 3 minutes. The infusion was then passed through a 20 mesh screen, followed by a 150 mesh screen and
10 cooled to $20-30^\circ\text{C}$. The infusion was then clarified using a centrifuge.
- (2) Sugar (5.5kg) was dissolved in hot water (6L), sterilised by UV treatment and added to the tea extract.
- (3) UHT-treated skimmed milk (10.6kg) was added to the
15 resulting mixture
- (4) Sodium ascorbate (0.05kg) was dissolved in water (2L) and the solution added to the mixture.
- (5) Water was added to a volume of 90L
- (6) The mixture was homogenised at $60-70^\circ\text{C}$ at 19.6kPa. [200
20 kgf.cm^{-2}] and heated to 85°C
- (7) Skimmed milk powder (1kg) was added and mixed at 13,500rpm for 2 minutes.
- (8) Sodium stearoyl lactylate (0.06kg) was added and mixed at 13,500 rpm for 2 minutes
- 25 (9) N-Creamer 46 modified starch (1.25kg - ex National Starch) was added and mixed at 13,500 rpm for 2 minutes at 65°C .
- (10) 0.2kg of milk protein hydrolysate (Hyfoama, ex. Quest) and dissolved thoroughly at 65°C

- 15 -

- (11) The resulting solution was cooled to 10°C and maltol (0.03kg) was added.
- (12) The solution was made to 100L with water.
- (13) The mixture (<295ml) was filled into standard 330ml beverage cans and sufficient liquid nitrogen was injected into the cans to give a head space pressure of 3.5 ± 0.2 bar at 5°C. The cans were then rapidly sealed.
- (14) The sealed cans were then retorted at 140°C for 5 minutes
- 10 The resulting beverage contained the following constituents

Constituent	% solids
Water	to 100%
UHT milk	10.60 %
Granulated sugar	5.5%
Sucrose esters (P1570)	0.1%
Hydrolysed milk protein (Hyfoama DS, Quest)	0.2%
Tea solids	0.2%
Skimmed milk powder	1%
Tea flavour mix 06	0.16%
Sodium ascorbate	0.05%
Maltol	0.03%
N-Creamer 46	1.25%
Sodium stearoyl lactylate	0.06%

- 16 -

Comparative Examples A and B

5

In a similar way to that described above in Example 3, samples of beverages which had the same constituents as Example 3 were prepared except that Comparative Example A did not contain any surface active agents and comparative Example B did not contain
10 any octenylsuccinic acid modified starch. The products were stored at 5°C for 3 hours and were then opened and poured into a graduated glass vessel. The amount of foam generated as the beverage was poured was determined from the graduations on the glass vessel. The amount of foam expressed as a percentage of
15 the volume of foam present immediately after pouring was determined periodically for the beverage of Example 3 and for both of the Comparative Examples A and B. The results are shown in the Table below

20

25

- 17 -

	Example 3	Example A	Example B
Foam volume	6.34%	6.66%	7.93%
Time (minutes)	Foam volume as % of volume at t_0		
2.5	100	100	100
5	100	75	100
10	100	50	60
15	100	50	44
20	100	50	20
30	95	40	20
40	90	35	12
60	90	25	8

5

From the Table it can be seen that the foam generated from Example 3 lasts considerably longer than the foam generated from either of the Comparative Examples.

10

- 18 -


CLAIMS

- 1) A beverage product comprising a container holding a liquid
beverage component and sufficient nitrogen gas to give a gas
5 pressure in the head space of at least 3.3 bar at 5°C, said
liquid beverage comprising an organoleptically acceptable
foam-maintaining system such that when the liquid beverage is
poured from the container a foam is generated, the volume of
which is maintained at greater than 80% of its initial volume
10 for a period of at least 10 minutes.
- 2) A beverage product as claimed in claim 1 wherein the volume
of the foam is maintained at greater than 80% of its initial
volume for a period of at least 30 minutes.
- 15 3) A beverage product as claimed in claim 1 wherein the initial
volume of the foam is less than 20% of the volume of the
liquid beverage.
- 20 4) A beverage product as claimed in claim 1 wherein the pressure
of nitrogen in the head space of the container is in the
range 3.3 to 6 bar at 5°C.
- 25 5) A beverage product as claimed in any one of claims 1 to 4
wherein the foam maintaining system of the liquid beverage
comprising 0.25 to 3.0% by weight of the liquid beverage
component of octenylsuccinic acid modified starch, and at
least one surface active agent selected from the group

- 19 -

consisting of acyl lactylate salts, proteins, protein hydrolysates and sucrose esters and mixtures thereof.

- 6) A beverage product as claimed in claim 5 wherein the
 5 octenylsuccinic acid modified starch is prepared by forming a covalent complex of a hydrophilic waxy maize starch with an octenylsuccinic acid moiety
- 7) A beverage product as claimed in claim 5 or claim 6 wherein
 10 the octenylsuccinic acid is a carboxy substituted undecenoic acid of formula



- 8) A beverage product as claimed in any one of claims 5 to 7
 20 wherein the percentage molar substitution of octenylsuccinic acid groups in the range of 1.9 to 3%.
- 9) A beverage product as claimed in any one of claims 5 to 8
 25 wherein molecular weight of the octenylsuccinic acid modified starch is in excess of 100,000 kDa.
- 10) A beverage product as claimed in any one of claims 5 to 9
 wherein the acyl moiety of the acyl lactylate salt contains 8
 to 16 carbon atoms.

30

- 20 -

- 11) A beverage product as claimed in any one of claims 5 to 10
wherein the acyl lactylate salt is a sodium or calcium salt
- 12) A beverage product as claimed in any one of claims 5 to 11
5 wherein the acyl lactylate salt is calcium stearoyl
lactylate, sodium stearoyl lactylate or mixtures thereof.
- 13) A beverage product as claimed in any one of claims 5 to 12
wherein the acyl lactylate salt comprises 0.005 to 1% by
10 weight of the liquid beverage.
- 14) A beverage product as claimed in any one of claims 5 to 13
wherein the proteins and protein hydrolysates are those
contained in or derived from milk
15
- 15) A beverage product as claimed in any one of claims 5 to 14
wherein the proteins and protein hydrolysates are selected
from sodium caseinate, whey protein isolates or milk protein
hydrolysates
20
- 16) A beverage product as claimed in any one of claims 5 to 15
wherein the sucrose ester is predominantly a monoester.
- 17) A beverage product as claimed in any one of claims 5 to 16
25 wherein the sucrose ester is prepared from sucrose and fatty
acids derived from edible fats and oils, said fatty acids
containing 8 to 16 carbon atoms

- 21 -

- 18) A beverage product as claimed in claim 17 wherein the fatty acid is caprylic acid, lauric acid, myristic acid, palmitic acid, stearic acid or mixtures thereof
- 5 19) A beverage product as claimed in any one of claims 5 to 18 wherein the sucrose ester comprises 0.02 to 0.4% by weight of the liquid beverage.
- 10 20) A method of making a beverage product comprising a container holding a liquid beverage component and nitrogen gas, said liquid beverage comprising an organoleptically acceptable foam-maintaining system, said method comprising the steps of:-
- 15 incorporating the organoleptically acceptable foam-maintaining system into the liquid beverage, placing the liquid beverage into the container, adding sufficient liquid nitrogen to the container to provide a head space pressure of 3.3 to 6 bar at 5°C in the container after sealing, and
- 20 sealing the container.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12606

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A23L2/40 A23L2/54

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23L B65B B01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, FSTA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 034 703 A (NESTLE SA) 13 September 2000 (2000-09-13) paragraph '0010!; claim 1; example 6 ---	1-4,20
A	US 4 279 938 A (HILDEBRAND PETER C R) 21 July 1981 (1981-07-21) claim 1 ---	1-20
A	US 5 853 782 A (LARSSON EBBE) 29 December 1998 (1998-12-29) page 1, column 1, paragraph 2; claim 1 ---	1-20
A	US 4 996 823 A (BYRNE WILLIAM J) 5 March 1991 (1991-03-05) claims 1,7,9 ---	1-20
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 February 2004

Date of mailing of the international search report

02/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Groh, B

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12606

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	W0 02 069981 A (TIC GUMS INC) 12 September 2002 (2002-09-12) page 2, paragraph 1 -page 4, paragraph 1 -----	5-19
A	AVIS J W ET AL: "THE USE OF NITROGEN TO IMPROVE BEER FOAM" PROCEEDINGS OF THE AVIEMORE CONFERENCE ON MALTING, BREWING AND DISTILLING, XX, XX, 19 May 1986 (1986-05-19), pages 347-351, XP001039846 page 349, paragraph 2 -----	1-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/12606

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1034703	A	13-09-2000	EP 1034703 A1	13-09-2000
			AT 242975 T	15-07-2003
			AU 2070500 A	14-09-2000
			BR 0000716 A	26-09-2000
			CN 1266010 A ,B	13-09-2000
			DE 69908901 D1	24-07-2003
			DE 69908901 T2	04-12-2003
			JP 2000253860 A	19-09-2000
			NZ 503029 A	31-08-2001
			PT 1034703 T	31-10-2003
			US 6669973 B1	30-12-2003
US 4279938	A	21-07-1981	NONE	
US 5853782	A	29-12-1998	SE 503788 C2	02-09-1996
			EP 0766516 A1	09-04-1997
			SE 9404210 A	06-06-1996
			WO 9617529 A1	13-06-1996
US 4996823	A	05-03-1991	GB 2222570 A	14-03-1990
			AT 78238 T	15-08-1992
			AU 632480 B2	07-01-1993
			AU 3402689 A	15-03-1990
			CA 1316808 C	27-04-1993
			DE 68902119 D1	20-08-1992
			DE 68902119 T2	25-02-1993
			EP 0360375 A1	28-03-1990
			ES 2034620 T3	01-04-1993
			GR 3005273 T3	24-05-1993
			IE 63100 B1	22-03-1995
			JP 2127221 A	15-05-1990
			NZ 228912 A	28-04-1992
WO 02069981	A	12-09-2002	US 6455512 B1	24-09-2002
			EP 1365773 A1	03-12-2003
			WO 02069981 A1	12-09-2002

